

M228

Rotawash

Colorfastness Tester

To determine color fastness to washing or dry cleaning to ISO, BSI AATCC and SDC standards. Fitted with programmer allowing automatic selection of all AATCC, ISO and other test methods with individual parameters displayed, select one of last 3 tests, select user defined program, COM port for updates. Now features a newly improved color touch control panel. Includes drain pump, inching facility and lid interlock. Washpots or accessories not included. M228B Capacity 8 washpots x 550ml or 8 x 1200ml. M228C Capacity 12 washpots x 550ml or 12 x 1200ml. M228P1 550ml Washpot with lid and seal. M228P2 1200ml Washpot with lid and seal.

Specifications	M228
Weight	75 kg
Dimensions	660 x 600 x 950 mm (WxDxH)
Standards	FTM S 191 METHOD 5610, FTM S 191 METHOD 5614, FTM S 191 METHOD 5622, AATCC 61/86/132/190, ISO 105-C01/105-C02/105-C03/105-C04/105-C06/105-C05, 105-C08/105-D01/105-C09/105-E03/105-E12, M&S C4A/C5/P3B /C10A/C11/C26, C37/C49A/P137, NEXT 2/2A/3/3A/5, IWSTW 7/115/177/193/199/240/241.



M228

■ To determine color fastness to washing or dry cleaning to ISO, BSI AATCC and SDC standards.